

## Data sheet

### Article Description

### **Double USB Charging Socket Series 9016**

Ready for use with insulating box,  
with black cable 2 x 1.0 mm<sup>2</sup>,  
length 2 m with Euro plug

Dimensions: LWH 60 x 60 x 49 mm  
Installation depth: 32 mm  
Installation diameter: 50 mm  
Protection class: IP20, for dry rooms only

#### **USB Charger:**

Input: 100 – 240 V AC  
Output: 5 – 12 V DC; 20 W max.  
Performance:

1 x USB A Quick Charge 3.0  
1 x USB C Power Delivery 3.0



<u>5,0 V</u>	<u>9,0 V</u>	<u>12,0 V</u>
3,0 A	2,22 A	1,67 A
3,0 A	2,22 A	1,67 A

C + A Output: 5,0 V; 3,0 A – 15 W Max  
Stand-by: 0,3 W

#### Ideal for vertical installation in front of example

- beside tables
- desks
- furniture
- kitchen

#### **Plug & Play**



Not suitable for flush-mounted wall installation, installation on worktops  
and use in damp rooms and outdoor areas.

The place of installation has to be chosen according to the installation instructions.

<i>inter BÄR-No.</i>	<i>Colour</i>
9016-014...	black
9016-018...	white

Technical modifications reserved!

inter BÄR GmbH + Co. KG, Hälverstraße 43, 58579 Schalksmühle, Germany,  
phone +49 2355 893-0, [www.interbaer.de](http://www.interbaer.de)